

MOVINCOOL TECHNICAL SPECIFICATION		Office Pro 63
Electronic Features	Control Panel	Programmable
	Thermostate Control	Electronic
Cooling Capacity	Rating conditions; 95°F at 60% RH	60,000 Btu/h
Electrical Characteristics	Voltage Requirement	3 Phase, 460V
	Total Power Consumption	6.6 kW
	Current Consumption	9.5 amps
	Recommended Fuse Size	20 amps
	NEMA Plug Configuration	L16-20
Fans	Motor Output-high/low	0.5/ 0.33 kW Evap.
		1.2/ 0.93 kW Cond.
Evaporator	Fan Type	Centrifugal
	Max. Air Flow-high/low	1940/ 1770 CFM
	Max. External Static Pressure	0.9 IWG
Condenser	Fan Type	Centrifugal
	Max. Air Flow-high/low	2830/ 2650 CFM
	Max. External Static Pressure	0.85 IWG
Compressor	Type	Hermetic Scroll
	Output	3.3 kW
Refrigerant*	Type	R-410A
Dimensions	W x D x H	30 x 52 x 64 in
Net Weight/Shipping Weight		705/ 835 lb
Power Cord	Gauge	12 AWG (4-core)
	Length	6 ft
Condensate Tank Capacity		Auto Pump Included
Operating Conditions	Min.-Max.(@50% RH)	65°F-105°F
Max. Equivalent Duct Length	Per Cold Duct Hose	40 ft
	Hot Duct Hose	100 ft
Max. Sound Level	With Condenser Duct - high/low	69/ 67 dB(A)
	Without Condenser Duct - high/low	71/ 69 dB(A)